





## BEAUREGARD

### FOR PRESCRIBERS

RoHS 
 ZD 
 IP 66 
 IK 10 
 Tool-less opening

PRODUCT NAME	BEAUREGARD
HOUSING	Four-legged holder in injected aluminium Fitting and dome in stainless steel or copper (option)
BOWL	6 bowls: PPC: flat clear polycarbonate bowl* PCC: shallow clear polycarbonate bowl PCS: shallow structured polycarbonate bowl PHC: deep clear polycarbonate bowl PHS: deep structured polycarbonate bowl PHO: deep opaline polycarbonate bowl *Only for light with BLS module
FINISH	Stainless stell version: polyester powder coating, standard colour RAL 9005. Other colours on request Copper fitting (option): polyester varnish
SOURCES	SOMLED 1 / BLS strips
COLOUR TEMPERATURE	SOMLED 1: 3000K or 4000K BLS strips: Amber**, 2200K, 2400K, 2700K, 3000K, 4000K
OPTICAL	ORALENS / QUADRALENS
FLUX & POWER**	Up to 10 984lm; 101W
ELECTRICAL CLASS	Class I or II
MOUNTING	Suspended and post top

\*Approx. 1800K

\*\*At 3000K, in accordance with performance standards IEC 62717 and IEC 62722 (+/-5%tolerance)



- ▶ Smart-ready® (Zd4i)
- ▶ Dimming
- ▶ Detection
- ▶ Moonlight technology
- ▶ Tunable white options
- ▶ WIZARD management system (pag. 420)


### MECHANICAL INTERFACES




POST TOP




SUSPENDED




Version PCS Bowl  
Supported version




Version VP Bowl  
Supported version




Version PPS Bowl  
Supported version



Version PCS Bowl  
Suspended version



Version VP Bowl  
Suspended version



Version PPS Bowl  
Suspended version