




KCC / RCE




Galvanised steel bracket

Light fixing: Ø 60 mm.

Tilt: 5° as standard, 10° or 15° on request.

Pole fixing: Ø 60 mm.

KCC	A mm	B mm	C mm	Tilt	Weight Kg	SCx m ²
Single light	250	122	-	5°	2.8	0.03
	500	145	-	5°	3.9	0.05
	1000	190	-	5°	6.0	0.08
	1500	234	-	5°	8.3	0.12
	2000	280	-	5°	14.1	0.16
Dual 180° light	250	122	500	5°	3.9	0.05
	500	145	1000	5°	6.0	0.08
	1000	190	2000	5°	10.5	0.16
	1500	234	3000	5°	14.8	0.23
	2000	280	4000	5°	25.9	0.30
Triple 120° light	250	122	500	5°	5.0	0.05
	500	145	1000	5°	8.3	0.08
	1000	190	2000	5°	14.8	0.16
	1500	234	3000	5°	21.4	0.23
	2000	280	4000	5°	37.7	0.30



Galvanised steel bracket

Light fixing: Ø 60 mm.

Tilt: 5° as standard, 10° or 15° on request.

Pole fixing: Ø 60 mm.

RCE	A mm	B mm	C mm	Tilt	Weight Kg	SCx m ²
Single light	1000	2000	-	5°	12.4	0.19
	1500	2000	-	5°	14.4	0.22
	2000	2000	-	5°	22.2	0.26
Twin light	1000	2000	-	5°	19.3	0.30
	1500	2000	-	5°	23.5	0.37
	2000	2000	-	5°	37.4	0.44
Triple light	1000	2000	-	5°	26.1	0.30
	1500	2000	-	5°	32.5	0.37
	2000	2000	-	5°	52.5	0.44