




Galvanised steel bracket, tilt 5°.  
 Light fixing: Ø 60 mm, Ø 27 pdg with ball joint or Ø 34 pdg with ball joint.  
 Bracket outreach: 0.70, 1.20 m and 1.50 m.

ECLATEC


#### Bracket **ARCOS GA**

Galvanised steel wall bracket, tilt 5°.  
 Plate fixing: 2 holes for anchors Ø 12 mm on a vertical spacing depending on the ridge.  
 Bracket outreach: 0.70 m and 1 m.  
 Light fixings: Ø 60 mm.  
 Pole: Concerto cylindrical-conical steel Ø 62 mm


## ARCOS GA 13



single light bracket  
1200



single light bracket  
700



wall bracket

ARCOS GA 13	A mm	B mm	C mm	D mm	Tilt	Weight Kg	SCx m <sup>2</sup>
Single light	700	1000	-	-	5°	10.9	0.17
	1200	1015	-	-	5°	16.5	0.26
	1500	1045	-	-	5°	17.8	0.28
Twin light	700	1000	1400	-	5°	15.4	0.25
	1200	1015	2400	-	5°	26.5	0.42
	1500	1045	3000	-	5°	29.1	0.47
Wall bracket	700	360	-	-	5°	-	-