



### SMART (options)

Smart-ready® (ZD4i)	✓
Night-time dimming	✓
Detection	✓
WIZARD remote management	✓

Details of the options and performance of each luminaire can be found in the ECLATEC LED solutions overview, which can be downloaded from our website: [www.eclatec.com](http://www.eclatec.com)

### DESCRIPTION

Model	ENZO 2
Luminaire body	Die-cast aluminium
Decorative design	BULLE, VENGA, LIN or customisable on request
Bowl	PPS : Structured Flat Polycarbonate MHC : High-clarity methacrylate with structured underside
Finish	Polyester powder coating, choice of colours
Shock resistance	IK10
	IP 66 as per the EN 60 529 standard
Leak tightness	Extruded silicone seal Luminaire 'breathes' through an active carbon filter
Dimensions (diam.)	Ø250 mm
Weight	5.7 kg
SCx	0.1 m²
Electrical rating	Class I or II
Ambient temperature	- 40°C to + 55°C
Pre-wired	Optional
Material assessment	PEP (Product Environmental Profile) sheet available on request


### MECHANICAL INTERFACES

Catenary	Tiltable catenary mounting $\pm 15^\circ$ — for cables with a diameter of 6 to 14 mm
Suspended	Pole-top nipple fixing Ø 27 PDG
Catelux	SM diam 27 PDG fastener, mechanical cable from 5 to 14 mm

### MAINTENANCE

Maintenance	Removal of the LED module from the lower part using 3 screws, safety cable Removable gear plate using 3 screws
-------------	---

### WIRED



### LED SOURCES

Sources	Barrettes BLS (8 to 16 LEDs) / AXEL (24 LEDs)
Colour temperature (K)	Amber/"1800 K" (U500=1%), 2200 K (U500=6%), 2700 K (U500=10%), 3000 K (U500=11%), 4000 K (U500=17%) (others on request)
CRI	> 70 (others on request)
Luminaire SDCM	<4
LED service life	L90 > 100,000 h
Optics and distributions	3 symmetrical lenses (ECL, ECa, ECb) 7 asymmetric lenses (ERE, ERS, ERL, LRS, LRL, LRM, ETS) 6 projection lenses (PFA, PSa, Paa, PFI, PFL, PFM) 2 pedestrian crossing lenses (EPG, EPD) 2 types of optional cut-off shields
Photobiology	RG1 (3000 K)

\* Partial list

### MAXIMUM PERFORMANCE (see LED synoptic for the other configurations)

	ENZO 2_PPS_AXEL (24 LED)		
	Flux <sup>(A)</sup> at 700 mA (lm)	Power <sup>(B)</sup> (W)	Efficiency (lm/W)
4000 K	7167	51	141
3000 K	6968	51	137
2700 K	6371	51	125
2200 K	5773	51	113
Amber/"1800 K"	4778	51	94

(A) Luminaire output flux at commissioning (including thermal and optical outputs relative to the source fluxes) for a given distribution and ambient temperature of 25°C in accordance with the IEC 62717 and IEC 62722 performance standards (B) Total power consumed by the luminaire including all electrical equipment, including the power supply in accordance with the IEC 62717 and IEC 62722 performance standards



DRIVERS

Power	220 V / 240 V - 50 Hz / 60 Hz / built-in 10 kV surge protection
Brand	PHILIPS Xitanium Full Prog or INVENTRONICS OSRAM 4 DIM - D4i version: SR, DEXAL or TRIDONIC PRE
Power factor	Greater than 90%
THD	Harmonic distortion of less than 15%
Current	Constant supply current adjustable up to 700mA* (in 1mA steps, within the nominal current range specified on the power supply data sheet)
Service life	Mortality: 10% maximum for 100,000 hours
Protocol	DALI or 1-10 V Protocols

\* I>700mA on request

STANDARDS / MARKINGS / CERTIFICATIONS

Compliance	<b>CE compulsory marking:</b> Directive 2014/35/EU, Low voltage Directive Directive 2014/130/EU Electromagnetic Compatibility Directive 2011/65/EU Directive 2009/125/EC Ecodesign requirements  French Decree 'limitation of light pollution' of 27 December 2018
	<b>Qualifies for energy savings certificates</b> C.E.E. forms, RES-EC-103, RES-EC 104
	<b>NF EN 13201</b> Relative to supplied lighting studies
	<b>REACH</b> Compliance of products and their manufacturing method with the Chemical Substance Management Regulatory framework
<b>WEEE</b>	WEEE (Waste electric and electronic equipment): manufacturer involvement
<b>ECOSYSTEM</b>	ECLATEC is a member

OPERATING GUARANTEE

Read the general terms and conditions of sale and guarantee on our website