

## CHENONCEAUX


## FOR PRESCRIBERS

✓RoHS **ZiDi** IP66 IK10


PRODUCT NAME	CHENONCEAUX II	CHENONCEAUX III
HOUSING	Aluminium or bronze/copper	
BOWL	3 polycarbonate bowls aluminium version: PHC: deep clear polycarbonate bowl PHS: deep structured polycarbonate bowl PHO: deep opaline polycarbonate bowl	
FINISH	Polyester powder coating, any colour available Varnish on copper	
SOURCES	CHENONCEAUX II	CHENONCEAUX III
COLOUR TEMPERATURE	3000K or 4000K	
OPTICAL	ORALENS	
FLUX & POWER**	Up to 5430lm; 45W	Up to 6723lm; 56W
ELECTRICAL CLASS	Class I or II	
MOUNTING	Suspended and post top	

\*Approx. 1800K

\*\*At 3000K, in accordance with performance standards IEC 62717 and IEC 62722 (+/-5%tolerance)



CHENONCEAUX II  
Post top



CHENONCEAUX II  
Suspended



CHENONCEAUX III  
Post top



CHENONCEAUX III  
Suspended



- ▶ Smart-ready® (Zd4i) only post top version
- ▶ Dimming
- ▶ Detection
- ▶ WIZARD management system (pag. 420)

## MECHANICAL INTERFACES



POST TOP



SUSPENDED